

FeasyBeacon

FSC-BP108 Datasheet



1. Description

FeasyBeacon FSC-BP108 is an innovative waterproof IP67 Bluetooth 5.1 Low Energy smart beacon, it simultaneously supports iBeacon, Eddystone (e.g. URL, UID, TLM), AltBeacon for broadcasting and provides the ability to advertise up to 10 slots of advertising frames.

With the iOS & Android FeasyBeacon SDK, the developers can take advantage of the flexibility of the SDK and focus on their own application, such as Broadcast, Proximity Marketing, Digital Signage, Indoor and Outdoor Location, Asset Tracking, Vehicle Tracking, etc. Meanwhile, FeasyBeacon SDK compiled app is available to download from both the iOS and Android platform (search 'FeasyBeacon' to download).



2. Features

- Waterproof, IP67
- Water-Drop-Shape Bluetooth Beacon with design patent
- Bluetooth 5.1 Compliant
- Pre-programmed with Feasycom Smart Beacon Firmware
- Up to 10 slots of Advertising Frames
- Portable Smart Beacon with 4 Years Battery Life (by Default Settings)
- Configurable by Free FeasyBeacon Mobile App and SDK
- Customizable Color, Logo, Hardware, Software

3. Functional Specifications

Item	Description
Advertising Format	Eddystone (URL/ UID/ TLM), iBeacon, AltBeacon
Configuring Method	FeasyBeacon SDK compiled app (e.g. FeasyBeacon app)
Advertising Interval	Default 1300 ms, range from 100 ms to 2000 ms
Security	Access password required, Default Pin Code 000000
Max Number of Broadcast	10 Slots configurable advertising frames
Default Broadcast Interval	1300 ms for iBeacon & Eddystone
System Compatibility	iOS 7.0+, Android 4.3+
Advertising Distance	Up to 400m (open area)
Firmware Upgrading	OTA (upgrade firmware over the air)

4. Product Specifications


Item	Description
Chipset	DA14531
Bluetooth Version	Bluetooth 5.1
TX power	-19.5 dBm to +2.5 dBm
Antenna	Ceramic antenna
Power Supply	CR3032
Battery Life	4 Years (ADV Interval = 1300 ms; TX Power = 0 dBm)
Material	ABS plastic
Color	White, Blue, Yellow, or customized
Size	48(L)mm x 37(W)mm x 7.8(H) mm
Net weight	15 g
Protection	IP67
Operating temperature	-20°C to +60°C

5. Configurable Parameters

Parameters in the below table are configurable by FeasyBeacon SDK compiled app (e.g. FeasyBeacon app), feel free to download FeasyBeacon app from Google Play App Store or iOS App Store.

Parameter		Description
Device Name		UTF-8 string, Default: FSC-BP108-XXXXXX
Pin Code		Access password to FSC-BP108 Default: 000000, Range: 000000 ~ 999999
Advertising Interval		Default: 1300 ms, Range: 100 ~ 2000 ms
Tx Power		Maximum Tx power: +2.5 dBm Default: 0 dBm, Range: -19.5 ~ 2.5 dBm
Eddystone-URL	URL	URL that needed to be advertising
	RSSI at 0m	A 1-byte value representing the average received signal strength at 0m from the advertiser (FSC-BP108), range: 0 ~ -127
Eddystone-UID	Namespace	10-byte Namespace
	Instance	6-byte Instance
	Reserved	Reserved for future use
	RSSI at 0m	A 1-byte value representing the average received signal strength at 0m from the advertiser (FSC-BP108), range: 0 ~ -127
iBeacon	UUID	16-byte UUID, e.g. FDA50693A4E24FB1AFCFC6EB07647825
	Major	2-byte Major, range: 0 ~ 65535
	Minor	2-byte Minor, range: 0 ~ 65535
	RSSI at 1m	A 1-byte value representing the average received signal strength at 1m from the advertiser (FSC-BP108), range: 0 ~ -127
AltBeacon	ID1	Beacon Identifier 1
	ID2	Beacon Identifier 2
	ID3	Beacon Identifier 3
	RSSI at 1m	A 1-byte value representing the average received signal strength at 1m from the advertiser (FSC-BP108), range: 0 ~ -127
	Manufacturer ID	The beacon device manufacturer's company identifier code
	Manufacturer Reserved	Reserved for use by the manufacturer to implement special features

6. Dimensions



7. Declaration

The contents of this datasheet are subject to change without prior notice for further improvement. Feasycom team reserves all the rights for the final explanation.

iBeacon is a trademark of Apple Inc., Eddystone is a trademark of Google Inc.

Indian Distributor Contact Details

CONTACT US

PENGYOU GLOBAL SYSTEMS AND SERVICES P LTD
11A, 5/357, G. Floor, Sri Narayana Nagar, Main Road,
Near Ajith Board Bus Stop, Kolapakkam,
CHENNAI - 600 128

Email: ga@pengyouglobal.com or
ga.pengyouglobal@gmail.com

Mobile: +91 99000 31795 or +91 87786 44854

